CONFIGURATION

System Type	Mini Full-Range system	
	Transducers	Acoustic Load
LMF - MHF	1 x 4 in (10 cm) woofer	Sealed



Operating Mode		
	Amplifier Channels	Supported Processing
	1: LMF - MHF	Armonia Plus (A+)

PERFORMANCE

Operating Range	130 Hz to 20 kHz +/-3 dB	Crossover points
LMF - MHF		130 Hz (built-in HPF)

Nominal Bandwidth			
H Coverage	90 deg. @ -6 dB point		
V Coverage	90 deg. @ -6 dB point		
Maximum SPL	Axial sensitivity (2.83V @ 1mt)	Continuos	Peak
LMF - MHF	92 dB	108 dB	114 dB

Input Impedance	
	Nominal
LMF - MHF	8 ohm

Rated Power	
	Recommended System High Pass Filter >> 130 Hz, 24 dB/octave Suggested System High Pass Filter >> 170 Hz, 24 dB/octave
LMF - MHF	40 Watts AES (80 Watts Program)

Operating Mode	Amplifier Channels	Supported Processing
LMF - MHF	1	Armonia Plus (A+)
	Max paired cabinets	Suggested Amplifiers
	4 Suggested	Powersoft Mezzo Series: Mezzo324, Mezzo604
	2 (4 Ω nom. load per ch.)	

Dimensions	W,H,D, (mm/in) Weight (Kg/lb)	IN & OUT Connections Description	Shell Construction Description
Height (Front)	130 mm/05.11 in	2 x Phoenix™	Cubic enclosure,
Height (Rear)	130 mm/05.11 in	Four Pins IN/OUT	Multi-laminate
Width (Front)	130 mm/05.11 in	paralleled connectors	birch ply 9/12 mm
Width (Rear)	130 mm/05.11 in	Pin Assignment:	Polyurea coated
Depth	130 mm/05.11 in	Pin 1 LMF - MHF pos.	paint
Weight	0.8 Kg/01.70 lb	Pin 2 LMF - MHF neg.	Perforated black
		Pin 3 THROUGH	protection grille
		Pin 4 THROUGH	

NOTICE!: Loud Professional reserves the right to alter specifications to the products and published documentations without notice