Smart Sub2.8R - Technical specifications

CONFIGURATION

System Type	Self-powered Sub-Bass enclosure	
	Transducers	Acoustic Load
LF1 - LF2	2 x 18 in (46 cm) woofer	Bass-Reflex

Operating Mode		
	Amplifier Channels	Supported Processing
	2: LF1, LF2	Armonia Plus (A+)

PERFORMANCE

Operating Range	32 Hz to 150 Hz +/-3 dB	Crossover points
LF1 - LF2		30 Hz - 80/120 Hz
HF		

Nominal Coverage	
	Omnidirectional

Maximum SPL	Axial sensitivity (2.83V @ 1mt)	Continuos	Peak
LF1 - LF2	104 dB	136 dB	142 dB

Input Impedance	
	Nominal
LF1 - LF2	8 + 8 ohm

Rated Power	
LF1 - LF2	750 + 750 Watts AES (1.500 + 1.500 Watts Program)

Operating Mode	Amplifier Channels	Supported Processing
LMF, MHF	2	Armonia Plus (A+)

Dimensions	W,H,D, (mm/in) Weight (Kg/lb)	IN & OUT Connections Description	Shell Construction Description
Height (Front) Height (Rear) Width (Front) Width (Rear) Depth Weight	1182.5 mm/23.97 in 1182.5 mm/23.97 in 575 mm/22.63 in 575 mm/22.63 in 730 mm/28.74 in 105 Kg/231 lb	2 x built-in Neutrik PowerCON™ - IN/OUT paralleled connectors 2 x built-in Neutrik™ XLR - IN/OUT paralleled connectors 1 x built-in ETH networking port	15° Trapezoidal Multi-laminate birch ply 18/24 mm Polyurea coated paint Perforated black protection grille

NOTICE!: Loud Professional reserves the right to alter specifications to the products and published documentations without notice